

Sensor connection cable

ACI113



Introduction


for digital MODBUS sensors CONDIX/PHIX with 8 pole cable socket brass plated and 7 pole pigtail, PU-cable



View product on our website

www.senseca.com/en/product/aci113-sensor-connection-cable

Circular connector, self assembly



for digital MODBUS sensors CONDIG/PHIX with 8 pole cable socket brass plated and 7 pole pigtail, PU-cable

Order Code

1.

2.

ACI - -


i Enter the code for your selected option in the order code field above. The numbering corresponds to the sets from which you can choose. Note that some options can only be used in certain combinations.

Nr.	Code	Description
1. Connection type	113	8-pin round plug connector M12x1
2. Connector material	00	Nickel plated brass
	VA	Stainless steel 1.4571

Available product variants

Ordercode	Description	Article No.
ACI113-VA	ACI113 Circular connector, self assembly (stainless steel) - Circular connector, 12pole socket (stainless steel) for self assembly	476331
ACI113-00	ACI113 circular connector, self assembly - Circular connector, 12pole socket (brass, nickel-plated) for self assembly.	476332

Sensor connection cable



for digital MODBUS sensors CONDIX/PHIX with 8 pole cable socket brass plated and 7 pole pigtail, PU-cable

Order Code

ACI - - - - **1**

i Enter the code for your selected option in the order code field above. The numbering corresponds to the sets from which you can choose. Note that some options can only be used in certain combinations.

Nr.	Code	Description
1. Connection type	113	8-pin round plug connector (socket contacts) M12x1\n open wire end ferrules
	114	8-pin round plug connector (socket contacts)\n and 8-pin contacts\n M12x1
2. Cable length	002	2 m
	005	5 m
	010	10 m
	025	25 m
3. Shielding	1	Shield not applied to coupling
4. Connector material	00	Nickel plated brass
	VA	Stainless steel 1.4571
	90	[90] CONDIX promotion version, incl. wiring and connectors for Power Supply, TPS and RS485 of GHM-ONE as well\nas power supply cable 3-wires.
	VA.LFi	Stainless steel 1.4571

Available product variants

Ordercode	Description	Article No.
ACI113-010-1-00	ACI113 sensor connection cable, 10m - for digital MODBUS sensors CONDIX/PHIX with 8 pole cable socket brass plated and 7 pole pigtail, PU-cable. Length: 10m	476117
ACI113-025-1-00	ACI113 sensor connection cable, 25m - for digital MODBUS sensors CONDIX/PHIX with 8 pole cable socket brass plated and 7 pole pigtail, PU-cable. Length: 25m	476118
ACI113-002-1-00	ACI113 sensor connection cable, 2m - for digital MODBUS sensors CONDIX/PHIX with 8 pole cable socket brass plated and 7 pole pigtail, PU-cable. Length: 2m	476533